



KMR DRILLING

"a hole lot better"

P O Box 156 Richmond, TAS 7025, Depot: 739 Colebrook Road Campania, TAS 7026
Phone / Fax: 03 6260 4122 Mobiles: 0419 588 375 or 0418 125 129, ABN: 27 565 707 813

HYDRAPOWER TREKKER 2100, CRAWLER MOUNTED – Rig 7 (All subject to final design)

Engine: Cummins 60Bhp

Rotary Drive Head:

2 speed with floating spindle for make up

High speed: Range 0 – 750 rpm

Max Torque 474Nm

Low speed: Range 0 – 150rpm

Max Torque: 2100Nm

Fitted with hydraulic head slide

Main Winch: Capacity 2500kg

Wire Line: Capacity 800kg

Pull Down: Pull out capacity: 4400kg
Pull down capacity: 3100kg

Hydraulics: Danfoss

Mast: Head travel: 2100m
Mast dump: 700mm

Angle Drilling: From Horizontal to vertical 90deg

Stabiliser Legs: 4 off with 700mm stroke

Fluid Pump: Bean: EO413

Tracked Undercarriage: Hinowa PT20G

Weight & Dimensions of Crawler & Rig:

Weight: 2400 – 2700kg

Length: 3.20m